

主要外形及连接法兰尺寸 Q641F(N、P、H、Y)-20K Main Outline and Connecting Flange Size

公称通径 Nominal diameter		外形尺寸 Outline Size			连接法兰尺寸 Connecting Flange Size							执行器型号 Actuator Model
mm	in	L	L ₁	L ₂	~H	D	D ₁	D ₂	C	f	n-Φd	
15	1/2	140	141/159	71/83	204/235	95	70	50	14	1	4-Φ15	AT050D/AT063S
20	3/4	152	141/159	71/83	209/240	100	75	58	16	1	4-Φ15	AT050D/AT063S
25	1	165	211/248	95/107	214/265	125	90	70	16	1	4-Φ19	AT075D/AT088S
32	1 1/4	178	248/269	107/123	269/287	135	100	80	18	2	4-Φ19	AT088D/AT100S
40	1 1/2	190	248/269	107/123	282/292	140	105	85	18	2	4-Φ19	AT088D/AT100S
50	2	216	269/315	123/141	290/325	155	120	100	18	2	8-Φ19	AT100D/AT115S
65	2 1/2	241	315/345	141/152	310/357	175	140	120	20	2	8-Φ19	AT115D/AT125S
80	3	283	345/409	152/172	346/368	200	160	135	22	2	8-Φ23	AT125D/AT145S
100	4	305	409/438	172/187	418/443	225	185	160	24	2	8-Φ23	AT145D/AT160S
125	5	381	438/550	187/215	460/503	270	225	195	26	2	8-Φ25	AT160D/AT190S
150	6	403	600/633	240/262	518/563	305	260	230	28	2	12-Φ25	AT210D/AT240S
200	8	502	633/730	262/330	583/618	350	305	275	30	2	12-Φ25	AT240D/AT270S

※注：球阀结构长度及连接法兰尺寸可根据用户要求设计制造。
 ※注：数执行器型号XXX/XXX 分别是气动执行器双作用式/单作用式(弹簧复位)。
 ※注：根据不同阀门扭矩、使用介质适配的执行器型号可能有所不同，相关尺寸随之变化。
 ※注：以上执行器配置及数据均采用软密封(F、N、P)阀门，硬密封阀门的配置及数据请咨询本公司。
 Note: The structural length and connecting flange size of ball valve series can be designed and manufactured as per users' requirements.
 Note: Data XXX/XXX represent respectively the double-acting/single-acting type(spring reposition)of pneumatic actuator
 Note: The relative sizes are subject to change responding to the difference in valve torque, medium and actuator model
 Note: the above actuator configuration and data all use soft-sealed valves (F, N, P) and hard-sealed valves, or consulting us if you have more questions.



气动固定式球阀

型号: Q647F(N、P、H、Y)
 口径: DN25-600mm
 压力: 1.6、2.5、4.0、6.4MPa; 150Lb、300Lb、600Lb; 10K、20K
 结构: 固定式
 尺寸标准: 国标、美标、日标
 阀体材质: 碳钢(WCB)、不锈钢(CF8、CF8M、CF3、CF3M)
 阀座材料: 聚四氟乙烯(F)、对位聚苯PPL(P)、尼龙(N)、硬质合金(H、Y)
 作用方式: 双作用、单作用(弹簧复位)
 控制方式: 开关型、调节型
 附件选择: 电磁阀、定位器、限位开关、气源处理三联件、手动机构

Pneumatic ball valve fixed
 Model: Q647F(N, P, H, Y)
 Bore: DN25-600mm
 Pressure: 1.6, 2.5, 4.0, 6.4Mpa; 150Lb, 300 Lb ,600 Lb; 10K, 20K
 Structure: Fixed
 Dimension standard: GB, American Standard, Japanese Standard
 Body material: Carbon steel (WCB) ,
 Stainless steel(CF8, CF8M, CF3, CF3M)
 Seat material: PTFE, PPL, H,Y
 Mode of action: the double-acting/ single-acting
 type(spring reposition) of pneumatic actuator
 Control: Switch type, Adjust type
 Selection of Accessories: solenoid valve ,Locator,
 Limit switch, F.R.L. COMBINATION UNIT, Manual Device.

